



- *UL Listed*
- *CSA Listed*
- *High Current in-rush*
- *2 inputs/outputs*
- *Solid State Design*
- *3-Year Warranty*

World Class Design

The **Command Access PS2BB power supply** is a high quality, cost effective solution for powering two electric latch pullback exit devices. This power supply provides the necessary surge current that most latch pullback exit devices require and battery backup to allow uninterrupted service. The PS2BB offers features found on much more expensive power supplies all with the solid-state design. The features, design and careful attention to detail make the PS2BB the ideal choice for the discerning user who requires a power supply that can offer years of trouble-free operation.



U.S. Customer Support
1-888-622-2377

Visit our website for more details
www.CommandAccess.com

Canada Customer Support
1-855-823-3002

MODELS AVAILABLE:

- PS2BB - Double Output power supply for latch pullback devices with battery backup

FEATURES:

- UL Listed
- CSA Listed
- Delivers the necessary in-rush current for two latch pullback exit devices
- Two independent inputs/outputs
- Solid-state design eliminates problems associated with mechanical relays
- Thermal overload sensing reduces risk of failure due to overheating
- Fire Alarm disconnect link
- Inputs triggered by dry contact
- Intelligent short circuit detection detects shorts much faster than glass or resettable fuses and isolates the short to the individual output
- Removable Euro-style terminal blocks allow for easy installation
- Efficient battery backup/charging circuitry with zero voltage drop at power loss
- Solid-state reverse polarity protection for battery connections
- Audible alert when sensing AC power failure & low battery (batteries not included)
- No hassle 3-Year Warranty

SPECIFICATIONS:

- Input Voltage - 120VAC
- Output Voltage - 24VDC regulated @ 2.3A
- Temperature range - 0 to 120 F
- 2 solid-state inputs/outputs (input triggered by dry contact)
- LED Indicators - Red = Power Indicator / Green = Channel on
- Enclosure Dimensions - 12.5" x 15" x 4" (accommodates two 7AH batteries - batteries not included)

Model No.	Notes:		
Customer:	Job No./Name:	Date:	Provided by: